

A10 EDGE CARD IDC TYPE (REINFORCED TYPE)

PITCH: 2.54mm

SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze or Brass

Electrical

Current Rating : 1 Amp DC




Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.


Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40℃ to +105℃

♦ Terminated with 1.27mm pitch flat ribbon cable.



POSITION	A	B
20	36.82	22.86
34	54.60	40.64



HOW TO ORDER:

A10 - 1 - 2 - 3 - 4 - 5

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.SPECIAL FUNCTION	5.INSULATOR COLOR
20 34	A: BRASS B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5μ" INCH GOLD B: 10μ" INCH GOLD C: 15μ" INCH GOLD D: 30μ" INCH GOLD	B: W/O STRAIN RELIEF W PLUGGED KEY D: W/O STRAIN RELIEF W/O PLUGGED KEY	1. BLACK 2. GREY